



# altro

## EcoFix™ 65 Spray

This spray adhesive may be used with Altro Lavencia Plus, Altro Quartz Tile, Altro Dolce and Altro Dolce Essentials

Coverage: 150 - 185 ft<sup>2</sup> (14 - 17.2 m<sup>2</sup>)

5 year warranty

Warranted for: 8lbs MVER, 98% RH, 11pH

### Product characteristics

Versatile spray adhesive naturally suited for adhering tile and/or plank products in commercial and residential applications.

Uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive. EcoFix 65's instant shear strength allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads. Suitable for areas with up to 98% RH.

Non-toxic, 0.020 g/ml VOC product that allows occupation of space as soon as installation is complete.

### Coverage guide

LVT, LVP, Tile - Upside down aerosol. 150-185 sq ft

Adhesive coverage is only an approximation based on experience, manufacturers recommendations, and subfloor texture and porosity, Altro does not warrant nor guarantee actual adhesive coverages.

### Advantages

- Uses 80% less adhesive
- Allows for all traffic immediately
- 0.020 g/ml VOC content
- Non-toxic, water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistant
- No offensive odors
- FloorScore certified

### Suitable substrates

Bonds Altro Lavencia to the following properly prepared, smooth, flat, dust-free substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT



### LEED facts

LEED v4

This product may help contribute to the following credits

EcoFix 65 Spray

1



Environmental quality  
Low emitting materials, adhesives

1

Discover more of our sustainability story and credentials at [altro.com](http://altro.com)

Technical data		Characteristics
Chemical type	Water-based acrylic blend	Provides immediate shear strength after installation allowing instant access to finished floor.
Appearance	Milky white frost bubbles	
Flash point	Will not burn	
NFPA 704 flammability rating	0 (Non-flammable)	Solvent free, emits no harmful fumes, and contains 0.020 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.
Shelf life	3 years, if unopened	
Open time	4 hours	
Dry time	Once adhesive is dry to touch (10-20 minutes)	Uses non-ozone depleting HFC propellant.
Foot traffic allowance	Immediately	
Heavy machinery allowance	Immediately	
Resistance to moisture	Excellent: 8 lbs/1,000 sq ft or 98% RH/11pH	Withstands 8 lbs. of vapor emissions, 98% RH and 11 pH.
Underfloor heating systems	Yes	
Storage	Do not subject to freezing temperatures	