

Altro XpressLay

The world's first adhesive-free slip-resistant floor that can save you money on materials and time on installation. Altro XpressLay is the next step in the evolution of slip-resistant flooring. It's installed using a tape system instead of adhesive, so it can be installed without a surface DPM. This means that you can weld the same day it is installed, greatly reducing installation time. It can be easily removed post-installation, reused elsewhere and then recycled at the end of its life.

Altro XpressLay includes a range of colors, with some available for quick ship in North America, featuring bright and subtle, sparkle-free designs and decorative chipped options. We know how important it is that your floor stays looking good year after year, so we've added Altro Easyclean for superior chemical and stain resistance.

Altro XpressLay also looks great paired with Altro Walkway 20, Altro Aquarius or Altro Wood.

Typical applications

General purpose, fast track, retrofits, education, temporary and historical buildings

Features + benefits

- World's first adhesive-free slip-resistant floor
- Installed with tape system, does not require surface DPM
- Easily removed post-installation for reuse and recycling
- Install in areas up to 98% relative humidity (A fully intact and efficient sub slab vapor barrier/retardant must be in place)
- Shares colors with popular Altro Walkway 20
- Can be walked on within 24 hours of installation
- Impressive chemical and stain resistance
- Achieves R10 slip resistance rating and SCoF of .78 dry, .80 wet
- FloorScore Certified / Low VOCs

Slip resistance









It is designers, specifiers and end-users' responsibility to ensure flooring is fit for purpose, and it's part of our role here at Altro to help make this process easy. Our flooring is separated into three categories: safety, slip-resistant and smooth.

Altro XpressLay is a slip-resistant flooring. It's a perfect choice for many commercial areas in which your slip risk is not as high as a commercial kitchen or other wet environments, but your patrons, patients, students and employees still deserve to be secure on their feet. Slip-resistant flooring from Altro will reduce the risk of slips, give you peace of mind and look good doing so.

Altro Easyclean EASYCLEAN



Rather than using a superficial surface coat, Altro Easyclean Technology is incorporated into the flooring while it is manufactured. This allows Altro flooring to benefit from enhanced cleaning and maintenance while still allowing our products' slip-resistant properties to shine through.

Smooth flooring will have a higher level of Altro Easyclean than a slip-resistant or safety floor.

- Industry-leading ease of cleaning
- Enhanced long-term cleanability
- Cleaning and maintenance cost savings
- Sustained long-term slip resistance
- Exceptional long-term durability
- Low dirt pick-up qualities
- Improved color retention


















Type + class		ASTM F1303	Type II, Grade 1, Class A, safety flooring
Thickness and wear layer		2.2mm .087" / .8mm wear layer, heterogeneous construction	
Roll dimensions		6'7" x 65'5" 2m x 20m	
Weight		4.79 lbs./yd 2.6 kg/m	
Warranty	10 year undert warmely	10 years	
Life expectancy	15 Vear In repositor	15 years	
Cleaning technology	EASYCLEAN"	Altro Easyclean	
Static coefficient of friction	.78D .80W SCOF	ASTM D2047	.78 dry, .80 wet
Dynamic coefficient of friction	.66 DCOF	ANSI/NFSI B101.3	.66 wet DCOF
Ramp test	R_{10}	DIN 51130	R10
TRRL pendulum test	PTV ≥36	BS 7976 ASTM E303	36+
Static load limit		ASTM F970	2000 psi
Indentation		EN 433	≤ 0.10mm
Wear (abrasion) resistance		EN 660	≤ 10% 50,000 cycles
Castor chair abrasion		EN 425	Pass
Flexibility	5	ASTM F137	Pass
Light fastness		EN 20105-B02	≥ 6
Sound insulation	(((©	ISO 140-8	7dB
Electrical behaviors	42.0 kV	EN 1815	≤ 2kV Antistatic
Minimum operating temperature		-4°F (-20°C)	
Fire and smoke performance	&	CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		ASTM F925	Tested
VOC emissions	floor score	CA 01350 FloorScore	Pass Certified
Bio-based content	branes	Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content	grandatel-free	Ortho-phthalate-free	
Recycled content	(This product contains 5% post-consumer recycled content.	
Composition	Aluminum trioxide and colored quartz aggregate throughout thickness. Silicon carbide also present on traditional "sparkly" hues. Altro Easyclean incorporated for exceptional cleanability.		
Backing	Non-woven polyester/cellulose glass fiber reinforcement scrim. Altro XpressLay has embossed PVC backing.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

Altro, Altro XpressLay, Altro Adhesive-free and Altro Easyclean are all trademarks of Altro Limited. Content was correct at time of creation. Altro reserves the right to change any detail. Please consult your sales representative for the latest product information. © Copyright Altro USA 2024



Discover more of our sustainability story and credentials at altro.com







Order samples 24 hours a day at altro.com and materialbank.com



These select quick-ship colors, are heavily stocked and consistently available in our North American warehouses.

Discover more online!



Maintenance guides



Illus. cleaning guides



Warranty forms



Literature



LEED forms



Installation guides



Installation quickfacts

Even more great resources!

- BIM components
- SDS sheets
- Detail drawings and CAD files
- High-resolution swatch downloads
- Photo galleries www.altropics.com
- Solutions by area type ORs, labs and cleanrooms, kitchens, senior living and more!

Follow us



- **USA** 800 377 5597
- © CANADA 800 565 4658
- www.altro.com

Content was correct at time of print. Altro reserves the right to change any detail. Please consult www.altro.com or your local Sales Representative for the latest product information