



altro

Designed for possibilities.
Made for people.



Adhesive-free flooring

Adhesive-free flooring ranges offering enhanced comfort underfoot, sound reduction and even slip resistance



Now that's
revolutionary

Your guide to selecting the right adhesive-free flooring for your commercial installation.





Adhesive-free flooring

Altro's award-winning, adhesive-free floors now feature new ranges offering you enhanced comfort under foot and greater impact sound reduction. With more color and wood-look options, these solutions provide complete flexibility for differing application areas and aesthetic appeal.

Teamed with the benefits of reduced installation time, cost savings and sustainable attributes, we invite you to discover how Altro adhesive-free is the next step in the evolution of commercial flooring.

Contents

Introduction	2
Solutions for any interior	3
Altro adhesive-free sheet flooring	5
Benefits of choosing Altro adhesive-free sheet flooring	6
Altro Cantata	11
Altro Wood adhesive-free	17
Altro XpressLay	23
Altro adhesive-free tile and plank flooring	29
Altro Ollero	31
Altro Lavencia Click	33



Richard Kahn, CEO and managing director of Altro offer remarks on adhesive-free flooring.

Clickable in PDF or visit altro.com

Solutions for any interior

Our award-winning adhesive-free flooring ranges have expanded to include smooth sheet flooring, slip-resistant options, rubber tile and LVT. Each of these solutions offer unique advantages that make them adaptable to your design's specific needs.

- Modern commercial aesthetic - Altro Cantata
- Wood-look, biophilic commercial aesthetic - Altro Wood adhesive-free
- Rugged, traditional commercial aesthetic - Altro XpressLay
- Underfoot comfort - Altro Cantata, Altro Wood adhesive-free, Altro Ollero
- One-in-a-million slip resistance - Altro Wood adhesive-free or Altro XpressLay
- Sound reduction - Altro Cantata or Altro Wood adhesive-free
- Residential housing needs - Altro Lavencia Click (special order)
- Extreme impact absorption - Altro Ollero

Altro Cantata™

Comfort-backed smooth sheet flooring
Tonal and modernist aesthetic
Altro Easyclean technology
14dB noise reduction
Withstands 1000 psi
Installs up to 98% RH*
Moderate slip resistance for a smooth floor
Sustainable - remove, reuse or recycle



Perfect in healthcare, senior living, education, retail, offices, general circulation areas, temporary health + modular builds

Altro Wood™ adhesive-free

Comfort-backed smooth sheet flooring
Home-like and biophilic aesthetic
Altro Easyclean technology
14dB noise reduction
Withstands 1000 psi
Installs up to 98% RH*
One-in-a-million slip resistance reassurance
Sustainable - remove, reuse or recycle



Perfect in healthcare, senior living, education, retail, offices, general circulation areas, temporary health + modular builds




Award-winning technology

The world's first adhesive-free + slip-resistant flooring

Altro XpressLay™

- Slip-resistant sheet flooring
- Traditional commercial aesthetic
- Altro EasyClean technology
- 7dB noise reduction
- Withstands 2000 psi
- Installs up to 98% RH*
- One-in-a-million slip resistance reassurance
- Sustainable - remove, reuse or recycle


Perfect as a general use slip-resistant floor including healthcare, education and temporary health + modular builds



Altro Ollero™

- Smooth rubber tile flooring
- Traditional commercial aesthetic
- Interlocking formats in 8mm, 10mm, 12mm
- Withstands 1000 psi
- Reduces foot fatigue, impact absorbing
- Sound absorbing - IIC 59+ (8mm and above)
- Made from 90% recycled materials

Perfect in leisure applications like health clubs, gyms, sport arenas as well as education, retail and amusement locations



Altro Lavencia™ Click

With additional consultation, we can build a **special order** LVT program that fits your unique adhesive-free needs...just ask your representative!

Choose one of our patterns, specify a thickness, wear layer and finish. With minimum orders as low as 10,500 square feet many commercial projects can take advantage of our customized program.

Perfect in housing, retail, offices, lobbies, reception, cafeterias, education and hospitality

*A fully intact and efficient sub slab vapor barrier/retardant must be in place.

Altro adhesive-free sheet flooring

Altro Cantata, Altro Wood adhesive-free and Altro XpressLay



Less downtime

With Altro adhesive-free sheet flooring, surface damp-proof membranes and adhesives are a thing of the past. Your installation can be up and ready in half the time of a traditional adhered sheet floor, letting you get back to business with minimal interruption to your schedule.

Damp problem? Not anymore!

The specially formulated studded underside emboss allows Altro adhesive-free sheet flooring to sit off the subfloor, allowing the floor to breathe, resulting in any moisture dissipating.

Fresh slab? No problem!

The revolutionary underside emboss means that Altro adhesive-free sheet flooring can be used on fresh concrete subfloors up to 98% relative humidity (RH)*.

There is no need to wait for new concrete to reach 90% RH, allowing you to install flooring quickly and easily without having to wait for the substrate to dry.

In some instances, Altro adhesive-free sheet flooring can be installed on floors that are between 7 - 10 days old.

Odor free

No glue means no adhesive odors – perfect in environments with many people living and working, and where shutting down shop or installing noisy extractor fans is simply not an option.

Install over existing flooring

Altro adhesive-free flooring can be installed over existing intact substrates without applying adhesive. This can save you thousands in expensive flooring removal and asbestos abatement.

*A fully intact and efficient sub slab vapor barrier/retardant must be in place.





Warrington Hospital, Altro XpressLay

in action

“I was unsure that the flooring would stay in place with all the heavy carts turning on it every day, but it has been designed to do just that, and hasn’t moved or buckled in the slightest. We are very impressed with Altro Cantata and we’ll certainly be recommending it for our future projects.”

.....
Dave Hunt

Cheshire Contract Flooring



Heavy rolling loads

Altro adhesive-free sheet flooring holds effectively. In fact, it has been tested with a 1,975lbs (900kg) drilling rig with caterpillar tracks. A patient on a hospital bed, utility carts, or heavy equipment is no problem at all!

Adhesive-free sheet flooring holds as effectively as Altro glue-down sheet flooring; no rucks, no movement. They achieve optimum installation results and conformity to our 10 year warranty!

Remove, reuse, recycle

Altro adhesive-free sheet flooring is 100% recyclable post-consumer and can be reused in other installations.

We have numerous success stories of re-purposing large format installations in which the floor is installed temporarily, lifted and used again in another temporary installation or permanently installed in local schools, shelters and soup kitchens.

At its end of life, Altro adhesive-free sheet flooring can be removed quickly and reused or recycled; there’s no flooring covered with adhesive and bits of substrate to deal with.

Access all areas

As Altro adhesive-free sheet floorings are not stuck down, it means you can easily lift up the flooring to access the subfloor – handy in cases of localized flooding or issues with the substrate. Also, any damage to the flooring itself can be quickly rectified. Just cut the flooring that needs replacing, patch the damage and install the new flooring.

How quick does it install?

Watch our time-lapse installation to see just how Altro adhesive-free sheet floorings can be installed overnight with minimal disruption.



Clickable in PDF format or navigate to altro.com

Does it really stay down without glue?

Watch our Altro Cantata be put to the test by our skeptical long-time customer...we gave him some material and he tried his best to ruck it up!



Clickable in PDF format or navigate to altro.com

How does the backing work?

Watch our animated video to see just how Altro adhesive-free sheet flooring allows moisture to escape.



Altro adhesive-free flooring provides a path for moisture to escape in a controlled manner.



Clickable in PDF format or navigate to altro.com

Lays flat, stays flat


Altro adhesive-free sheet flooring lays flat without an adhesive to stick it in place. So you can roll away – without the floor rolling up.

Straight to slab... or tiles...or vinyl

Altro Cantata can be laid over existing sound substrates without applying adhesive. So you can weld and walk on the floor the same day.

Moisture problem... not anymore!


The specially formulated studded underside emboss allows flooring to sit off the subfloor, allowing the floor to breathe, resulting in any moisture dissipating. It can be used with a new concrete floor at up to 98% relative humidity*.



Fit, tape, weld - an ultra quick installation

Most resilient floors require you to wait a minimum of 24 hours before heat-welding and 72 hours before they can receive heavy traffic. With Altro adhesive-free sheet flooring, you don't have to wait for adhesives to cure.

Just install, weld and walk on the same day. You can plan builds in stages without being held up by drying times.



*A fully intact and efficient sub slab vapor barrier/retardant must be in place.



Altro Cantata

Altro Cantata is a tonal and modernist, adhesive-free floor that creates maximum impact with minimum downtime. It is ideal for busy public spaces where disruption needs to be minimal, and has no associated adhesive odors. Using our award-winning adhesive-free installation method, it can be welded and walked on the same day, and at the end of its life can be removed easily, allowing it to be reused or recycled.

Altro Cantata also looks great paired with Altro Wood adhesive-free, Altro Aquarius and Altro Orchestra.

Typical applications

Healthcare, temporary healthcare, modular buildings, historical buildings, senior living, education, retail and offices, hallways, general circulation areas

Features + benefits

- Underfoot comfort and sound reduction - 14dB
- Quickly installs with tape for minimal downtime
- Can be welded and walked on same day
- Install in areas up to 98% relative humidity*
- Embossed backing allows moisture to dissipate
- No adhesive odors
- Easy removal - uplift, reuse and recycle
- Contains rapidly renewable bio-based content
- Emits low VOCs

Better together

Smooth flooring from Altro gives you what you want - an economical and attractive look that's easy to install and maintain. But, in commercial areas with frequent spillages as well as hygiene and durability concerns, it's best to let our robust collection of safety flooring, slip-resistant flooring and wall cladding join the team!

2.4mm
thick

6'7"
width


65'5"
length

sheet
format


*A fully intact and efficient sub slab vapor barrier/retardant must be in place.









Crème Caramel WR385 / A1M385
AFP282006 LRV 50




Mocha WR389 / A1M389
AFP282003 LRV 40




Treviso WR483 / A1M483
AFT284003 LRV 44




Hazelnut WR418 / A1M239
AFP282009 LRV 18




Bluefin WR438 / A1M486
AFC281001 LRV 26




Bluebell WR398 / A1M398
AFP282004 LRV 26




Milan WR482 / A1M482
AFT284002 LRV 15



Willow Tree WR399 / A1M399
AFP282007 LRV 41




Frosted Glass WR388 / A1M388
AFP282005 LRV 52



Venice WR484 / A1M484
AFT284004 LRV 40




Seal Grey WR435 / A1M390
AFC281002 LRV 26




Graphite WR390 / A1M390
AFP282002 LRV 30




Elephant Grey WR436 / A1M487
AFC281003 LRV 17



True Grit WR391 / A1M82
AFP282001 LRV 17



Rome WR481 / A1M83
AFT284001 LRV 16



Black Sand WR485 / A1M485
AFP282010 LRV 7

Always approve a physical sample before placing a material order. Image quality can vary and small swatches may not show the full pattern.

LEED facts




LEED v4 This product may help contribute to the following credits

Altro Cantata 4

- Materials and resources
Renewable bio-based content 1
- Materials and resources
Environmental product declaration 1
- Materials and resources
Health product declaration 1
- Environmental quality
Low emitting materials, flooring 1

Discover more of our sustainability story and credentials at altro.com



Sunrise WR393 / A1M393
AFP282008 LRV 19

Specifications

Type + class		ASTM F1303	Type I, Grade 1, Class C, smooth flooring
Thickness and wear layer		2.4mm .09" / .7mm / 28 mil wear layer, heterogeneous construction	
Roll dimensions		6'7" x 65'5" 2m x 20m	
Weight		4.42 lbs./yd ² 2.4 kg/m ²	
Warranty		10 years	
Cleaning technology		Altro Easyclean	
Dynamic coefficient of friction		.70 .79D .94W	ANSI/NFSI B101.3 Altro Cantata .70 wet DCoF
Static coefficient of friction		.79D .94W	ASTM D2047 .79 dry, .94 wet SCoF
Ramp test		R10	DIN 51130 R10
TRRL pendulum test		PTV ≥36	BS 7976 36+
Static load limit		ASTM F970	1000 psi
Residual indentation		EN ISO24343-1	≤ 0.20mm
Wear (abrasion) resistance		EN 660	Group T
Castor chair abrasion		EN 425	Pass
Flexibility		EN ISO 24344	Pass
Light fastness		EN ISO 105-B02	≥ 6
Sound insulation		EN ISO 10140-3	14dB
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		EN ISO 26987	Good
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Composition	Heterogeneous PVC with glass fiber reinforcement scrim between the film print and backing. Altro Easyclean incorporated into top layer for exceptional cleanability.		
Backing	Embossed PVC backing.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at altro.com , training clinic information at altro.com . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at altro.com . Failure to install, heat weld, and/or maintain correctly could void the warranty.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		



Altro Wood adhesive-free

Altro Wood adhesive-free creates maximum impact with minimum downtime. With many color choices, 14dB sound reduction, a 10-year warranty and our Altro one-in-a-million slip resistance reassurance, Altro Wood adhesive-free offers high levels of comfort underfoot providing a safe, durable and decorative solution for busy spaces.

Using our award-winning adhesive-free installation method, it can be welded and walked on the same day, and at the end of its life can be removed easily, allowing it to be reused or recycled. Using Altro adhesive-free floors, you can halve installation time compared with a traditional adhered installation. It is ideal for busy public spaces where disruption needs to be minimal, plus there are no associated adhesive odors.

Typical applications

Healthcare, temporary healthcare, modular buildings, historical buildings, senior living, education, retail and offices, hallways, general circulation areas

Features + benefits

- One-in-a-million slip resistance reassurance
- Underfoot comfort and sound reduction - 14dB
- Quickly installs with tape for minimal downtime
- Can be welded and walked on same day
- Install in areas up to 98% relative humidity*
- Embossed backing allows moisture to dissipate
- No adhesive odors
- Easy removal - uplift, reuse and recycle
- Contains rapidly renewable bio-based content
- Emits low VOCs
- Authentic looking wood-grain visuals
- Has matching looks in 2mm, 2.85mm and 3.9mm

2.4mm
thick

6'7"
width

65'5"
length

sheet
format

*A fully intact and efficient sub slab vapor barrier/retardant must be in place.







AF Bleach. Oak WR335 / A1M335
AFW280001 **LRV 52**



AF Castle Oak WR335 / A1M335
AFW280013 **LRV 51**



AF Wash. Oak WR347 / A1M347
AFW280007 **LRV 38**



AF Slate Oak WR322 / A1M390
AFW280018 **LRV 26**



AF Vint. Cherry WR336 / A1M239
AFW280003 **LRV 22**




AF Urb. Cherry WR337 / A1M337
AFW280004 **LRV 17**



AF Worn Oak WR322 / A1M239
AFW280012 **LRV 19**



AF Manor Oak WR348 / A1M348
AFW280008 **LRV 7**



AF Rustic Oak WR340 / A1M340
AFW280005 **LRV 37**



AF Oak Trad. WR353 / A1M225
AFW280006 **LRV 25**



AF Spg. Maple WR352 / A1M352
AFW280011 **LRV 27**



AF Honey Oak WR352 / A1M352
AFW280017 **LRV 21**



AF Farm. Oak WR338 / A1M338
AFW280010 **LRV 38**



AF Aut. Maple WR339 / A1M339
AFW280002 **LRV 24**



AF Bav. Oak WR514 / A1M514
AFW280015 **LRV 21**



AF Sessile Oak WR350 / A1M483
AFW280016 **LRV 30**

Always approve a physical sample before placing a material order. Image quality can vary and small swatches may not show the full pattern.

LEED facts



LEED v4 This product may help contribute to the following credits

Altro Wood adhesive-free 4

- Materials and resources
Renewable bio-based content 1
- Materials and resources
Environmental product declaration 1
- Materials and resources
Health product declaration 1
- Environmental quality
Low emitting materials, flooring 1

Discover more of our sustainability story and credentials at altro.com



AF Ant. Walnut WR341 / A1M160
AFW280009 LRV 15



AF Great Oak WR339 / A1M339
AFW280014 LRV 22

Type + class		ASTM F1303	Type I, Grade 1, Class C, smooth flooring
Thickness and wear layer		2.4mm .09" / .7mm / 28 mil wear layer, heterogeneous construction	
Roll dimensions		6'7" x 65'5" 2m x 20m	
Weight		4.42 lbs./yd ² 2.4 kg/m ²	
Warranty		10 years	
Cleaning technology		Altro Easyclean	
Dynamic coefficient of friction		ANSI/NFSI B101.3	.49 wet DCoF
Static coefficient of friction		ASTM D2047	.79 dry, .94 wet SCoF
Ramp test		DIN 51130	R10
TRRL pendulum test		BS 7976	36+
Static load limit		ASTM F970	1000 psi
Residual indentation		EN ISO24343-1	≤ 0.20mm
Wear (abrasion) resistance		EN 660	Group T
Castor chair abrasion		EN 425	Pass
Flexibility		EN ISO 24344	Pass
Light fastness		EN ISO 105-B02	≥ 6
Sound insulation		EN ISO 10140-3	14dB
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		EN ISO 26987	Good
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Composition	Heterogeneous PVC with glass fiber reinforcement scrim between the film print and backing. Altro Easyclean incorporated into top layer for exceptional cleanability.		
Backing	Embossed PVC backing.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at altro.com , training clinic information at altro.com . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at altro.com . Failure to install, heat weld, and/or maintain correctly could void the warranty.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		



in action

“We have used other Altro adhesive-free floors for a few years now, and the new Altro Wood adhesive-free product is fantastic... It looks great, and it complements the care home perfectly. Installation is so much quicker because we are not waiting for adhesives to cure and it can go straight down onto the existing floor, so there is minimal disruption for residents.”

.....
Roo Williams
C + C Flooring

Clickable in PDF format or navigate to altro.com





Altro XpressLay

The world's first adhesive-free safety floor that can save you money on materials and time on installation. Altro XpressLay is the next step in the evolution of safety flooring. It's installed using a tape system instead of adhesive, so it can be installed without a surface DPM. This means that you can weld the same day it is installed, greatly reducing installation time. It can be easily removed post-installation, reused elsewhere and then recycled at the end of its life.

Altro XpressLay includes a range of colors featuring bright and subtle, sparkle-free designs and decorative chipped options. We know how important it is that your floor stays looking good year after year, so we've added Altro Easyclean for superior chemical and stain resistance.

Altro XpressLay also looks great paired with Altro Walkway™ 20, Altro Aquarius or Altro Wood™.

Typical applications

General purpose, fast track, retrofits, education, temporary healthcare, modular and historical buildings

Features + benefits

- One-in-a-million slip resistance reassurance
- Quickly installs with tape for minimal downtime
- Can be welded and walked on same day
- Install in areas up to 98% relative humidity*
- Embossed backing allows moisture to dissipate
- No adhesive odors
- Easy removal - uplift, reuse and recycle
- Contains rapidly renewable bio-based content
- Emits low VOCs
- Coordinates with popular Altro Walkway 20 range

2.2mm
thick


6'7"
width


65'5"
length

sheet
format


*A fully intact and efficient sub slab vapor barrier/retardant must be in place.









Blizzard XLI2255
WR79 / A1M191 LRV 44




Streetlight XLI2205P
WR287 / A1M79 LRV 45




Temple XL2209P
WR261 / A1M81 LRV 27




Whale XLI2254
WR86 / A1M86 LRV 20




Fog XLI22153
WR81 / A1M81 LRV 27




Dolphin XL2210
WR86 / A1M86 LRV 21




Pavement XLI2207P
WR83 / A1M83 LRV 14




Runway XL2206P
WR72 / A1M72 LRV 9




Nightfall XLI2256
WR72 / A1M72 LRV 10




Black XLI22892
WR100 / A1M100 LRV 6




Coal XLI2258
WR100 / A1M100 LRV 6




Swan XLI2212P
WR291 / A1M01 LRV 75




Minster XL2218P
WR289 / A1M265 LRV 40




Sand XLI2251
WR20 / A1M20 LRV 40




Bone XL22215
WR20 / A1M20 LRV 37




Biscuit XL22907
WR146 / A1M20 LRV 30




Tundra XL22910
WR153 / A1M239 LRV 17



Tango XL2231
WR42 / A1M42 LRV 14



Tarragon XLI2252
WR52 / A1M52 LRV 26



River XLI2257
WR71 / A1M71 LRV 22



Type + class		ASTM F1303	Type II, Grade 1, Class A, safety flooring
Thickness and wear layer		2.2mm .087" / .8mm wear layer, heterogeneous construction	
Roll dimensions		6'7" x 65'5" 2m x 20m	
Weight		4.79 lbs./yd ² 2.6 kg/m ²	
Warranty		10 years	
Cleaning technology		Altro Easyclean	
Static coefficient of friction		ASTM D2047	.78 dry, .80 wet
Dynamic coefficient of friction		ANSI/NFSI B101.3	.66 wet DCOF
Ramp test		DIN 51130	R10
TRRL pendulum test		BS 7976 ASTM E303	36+
Static load limit		ASTM F970	2000 psi
Indentation		EN 433	≤ 0.10mm
Wear (abrasion) resistance		EN 660	≤ 10% 50,000 cycles
Castor chair abrasion		EN 425	Pass
Flexibility		ASTM F137	Pass
Light fastness		EN 20105-B02	≥ 6
Sound insulation		ISO 140-8	7dB
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Minimum operating temperature		-4°F (-20°C)	
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		ASTM F925	Tested
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Recycled content		This product contains 5% post-consumer recycled content.	
Composition	Aluminum trioxide and colored quartz aggregate throughout thickness. Silicon carbide also present on traditional "sparkly" hues. Altro Easyclean incorporated for exceptional cleanability.		
Backing	Non-woven polyester/cellulose glass fiber reinforcement scrim. Altro XpressLay has embossed PVC backing.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at altro.com , training clinic information at altro.com . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at altro.com . Failure to install, heat weld, and/or maintain correctly could void the warranty.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

LEED facts

LEED v4 This product may help contribute to the following credits

Altro XpressLay **5**

- Materials and resources
Contains recycled content **1**

- Materials and resources
Renewable bio-based content **1**

- Materials and resources - EPD
Environmental product declaration
Type III product specific **1**

- Materials and resources - HPD
Health product declaration **1**

- Environmental quality
Low emitting materials, flooring **1**

Discover more of our sustainability story and credentials at altro.com



These select quick-ship colors, are heavily stocked and consistently available in our North American warehouses.



Adhesive-free tile + lvt options

Altro Ollero and Altro Lavencia Click (special order)



Not just sheet flooring

In addition to our adhesive-free sheet flooring ranges, we offer economically priced and easy-to-install rubber tile and LVT solutions with their own unique benefits.

Looking to create a warm, welcoming home-like aesthetic in a range of application areas, or for a way to provide lasting durability in busy recreational spaces? Altro has you covered:

- Quick, efficient installation via interlocking format
- Varying sizes + thickness options available
- Easy-to-clean, no additional finish or wax required
- High indentation resistance
- Impressive commercial durability
- Reduces sound transmission
- Made in North America
- Stocked locally throughout the US + Canada
- Economically priced

The flooring installer, Diverzify, requested a 5mm thick custom LVT to avoid needing a cork or similar underlayment for extra sound resistance, cost and time savings. Our special order program allowed them to finish the 350,000 square foot installation six weeks before the scheduled completion date.

.....
Spoke Apartments
Chicago, Illinois

in action

Altro Ollero

Altro Ollero is a versatile, durable and eco-friendly rubber flooring solution designed to provide the look of more traditional commercial surfaces such as carpet, stone and even cork. Available in a range of 22 colors with a mixture of solid, speckled, neutral and vibrant tones, these tiles are guaranteed not to curl, harden or crack over time. Their integrated impact and sound absorption properties can help reduce fatigue and excess noise in high traffic areas.

With no need for additional finishes or wax, Altro Ollero is easy to clean and maintain without the use of harsh chemicals, making it a cost efficient option for retail, education and recreational areas. These precision water-jet cut tiles are easy to install and come in a square-edge glue-down format or an adhesive-free interlocking format.

Typical applications

Retail, leisure, fitness centers, sporting arenas, education, childcare, gymnasiums, museums, libraries, amusements centers

Features + benefits

- Easy-to-clean
- Reduces fatigue
- Impact and sound absorbing
- High SCoF values wet or dry
- Long life expectancy + 10 year warranty
- Guaranteed not to curl
- High traction and durability
- FloorScore Certified

Altro Ollero contains as much as 90% post-consumer recycled content. Manufactured locally using reclaimed SBR rubber found in commercial truck tires, this product is FloorScore certified for low VOCs.

Thickness

- **4mm** is great for general use with a fantastic cost-efficiency (**glue-down installation only**)
- **8mm** increases comfort underfoot and is more suitable for sport and high traffic areas
- **10mm** offers further enhanced comfort and optimal ergonomic properties for long periods of standing. It is also fantastic for use with ski boots, cleats, and hockey skates
- **12mm** allows consistent intense demand on the floor in areas like heavy-duty fitness centers and gyms

Formats

Available in both glue-down and adhesive-free formats.



Square tiles

38" x 38"
Glue-down installation



Interlocking tiles

37" x 37"
Adhesive-free installation

Altro Ollero is available in adhesive-free interlocking tiles in thicknesses 8mm and above!



For additional information, technical specifications and swatches please view the Altro Ollero webpage.



Altro Lavencia Click

Attractive looks and lasting durability are not the only traits that make Altro Lavencia the premier LVT for commercial applications — Altro Lavencia is now proudly manufactured in the USA!

Available in an extensive palette of updated films ranging from classic wood tones, coordinating stones, brights and even modern organic looks, Altro Lavencia is a stylish, low-maintenance option for a host of application areas.

Peak beauty and performance will last through its lifetime, even in areas with consistently heavy traffic, thanks to the commercial-grade finish and wear layer.

Typical applications

Schools, colleges, offices, government buildings, senior living, public housing, apartment communities, retail, dining rooms

Features + benefits

- Special order our standard range in adhesive-free click options
- UV-cured, ceramic reinforced finish
- Resists up to 2000psi of indentation
- Easy-to-clean, no finish required
- Square edge construction - means no bevel for dirt to hide in
- FloorScore Certified
- Ortho-phthalate-free
- Made in the USA
- Stocked throughout the USA + Canada



Sizes

- 6" x 48" standard plank
- 9.25" x 59.25" long plank
- 12" x 24" tile
- The size that is listed for our traditional glue-down product must carry-over to the special order product as well.

Custom capabilities

Thanks to local manufacturing innovations, we are now able to offer Altro Lavencia in **special order** options, including adhesive-free click!

The I4F patented click technology provides industry leading performance with high locking strength and a 30% quicker installation free of hassles and special tools.

Choose one of our patterns, specify a thickness, wear layer and finish. With minimum orders as low as 10,500 square feet many commercial projects take advantage of our customized LVT program.

*10,500 square foot minimum order on custom orders.
Warranty terms may vary based on custom specification.*



For additional information, technical specifications and swatches please view the Altro Lavencia webpage.



Cleaning

Proper cleaning is essential to keeping a facility hygienic no matter which interior finishes are selected. We highly recommend that a cleaning and sanitizing program is created specific to your facility that utilizes the resources and products as recommend by individual manufacturers.

Our cleaning guidelines are available at altro.com

Samples

Altro recommends that color selection is never made through printed or digital materials. Please order a physical sample for color and pattern approval before placing your order with us.

Order samples 24 hours a day at altro.com or find us on Material Bank.



📞 **USA** 800 377 5597

📞 **CANADA** 800 565 4658

✉️ support@altro.com

🌐 www.altro.com

Content was correct at time of print. Altro reserves the right to change any detail. Please consult www.altro.com or your local Sales Representative for the latest product information.